

n e s i t e

raising your projects



resin surface

## 4.0

ENHANCE YOUR PROJECT WITH MORE COLOR POSSIBILITIES,

CHOOSE THE COLOR OF YOUR FLOOR IN FULL FREEDOM

4.0 is the raised floor panel with high density calcium sulphate core, finished with a pigmented heterogeneous resin which, after drying, forms an anti-scratch and shock-resistant film.

### CUSTOMIZATION


With 4.0 you can decide:

- **Colour** - in addition to the Nesite collection, it's possible to create the 4.0 floor by choosing the colour directly from the RAL scale.
- **Opacity** - 4.0 is available in glossy, semi-gloss and opaque version.
- **Finishing** - standard or embossed, for a greater slipping resistance.
- **Graphic elements** - inserted through a particular production process, for a further customization of the floor.

NESITE COLLECTION




MILK CONCRETE



WHITE 9003




GREY WHALE



SILVER GREY 7044



AGATE GREY 7038



STONE GREY 7030



TECHNICAL CHARACTERISTICS

TEST	STANDARD	RESULT
Resistance to cold liquids for cleaning	PTP53:2017 Rev.2	approved (CATAS)
Resistance to cold liquids acids and stains	UNI EN 12720:2013	approved (CATAS)
Abrasion resistance	UNI EN 15185:2011	class B
Scratch resistance	UNI EN 15186 :2011	class A
Fire safety	EN13501 -1	class Bfl,s1
Anti-slip	B.C.R.A	approved
V.O.C	UNI EN ISO 16000-9:2006	Formaldehyde-free panel (CATAS)
	ISO 16000-6:2011	

## MAINTENANCE

### First cleaning

Product:	NESITE CLEAN'UP (FILA CLEANER) diluted 1:10
Quantity:	1/2 liters for 100 square meters, depending on the degree of dirt
Equipment::	mop or clean cloth
Procedure:	Wash using NESITE CLEAN'UP diluted in water. If possible, use warm water and wring out the mop well by rinsing it often in the detergent solution. Pay attention to electrical and telephone distribution systems; do not use water to clean the subfloor.

### Regular maintenance

Product:	NESITE CLEAN'UP (FILA CLEANER) diluted 1:50
Quantity:	NESITE CLEAN'UP 1/2 liters for 100 sqm
Equipment::	mop or clean cloth
Procedure:	Wash using NESITE CLEAN'UP diluted in water (1 glass in 5 L). If possible, use warm water and wring out the mop well by rinsing it often in the detergent solution. Pay attention to electrical and telephone distribution systems; do not use water to clean the subfloor

**N.B:** use soft wheels W type (EN12529) and/or an appropriate office mat.



**n e s i t e**

raising your projects

Transpack Group Service S.p.a  
via San Marco, 11 - 35129 (PD)

**production unit:**

via Dell'Industria, 19 - 35028

Piove di Sacco (PD) - Italy

+39 049 807 25 36

nesite@nesite.com

nesite.com